

GLOBAL  
STAC<sup>®</sup>  
LIVE



cpacket  
NETWORKS

VISIBILITY YOU CAN TRUST

LOREM  
+0.7844

IPSUM  
-4.5489

DOLOR  
+6.2035

SIT  
-0.8965

AMET  
+3.0293

CONSECT  
-9.2904

ADIPISCING  
-8.3748

+Add



# Future-Proof Transition to Cloud with Unified Observability Strategy

Andy Idsinga  
Cloud Engineering Manager,  
Sr. Cloud Architect

# cCloud™ Visibility Suite

cVu-V in “inline mode” **captures traffic between subnets** or VNET/VPCs of interest - packets are not touched as they are routed through the appliance.

cVu-V in “endpoint” mode receives packets from the **cloud provided traffic/packet mirroring** feature

cClear-V provides single pane of glass **management and analytics** for all cPacket appliances. Pulling required data from **clusters of cPacket appliances**

cCloud appliances are designed to scale vertically and horizontally. Initialized using cloud-init for **immediate operation on boot** and integration with **devops config. mgmt**

cVu-V **forwards** traffic to **downstream tools** encapsulated in VxLAN.

cVu-V **replicates** packets to tools that provide different functionality - i.e. storage, security, custom financial use cases

Tools that process packet and analytics output


cStor-V performs **real-time analytics as packets arrive** : provides **search and download APIs** for accessing raw packets or metadata

Analytics, Provisioning, and Management

Packet Capture and Analysis

# cCloud™ Visibility Suite

Analyzing a distributed, real-time data processing and delivery application (financial services)

















azure\_vnet : 10.0.1.141

0 B


6 MB






## cCloud appliance metrics


cVu-V CPU (azure monitor)




cClear-1 CPU (azure monitor)




cStor-1 CPU (azure monitor)



cStor-1 disk (azure monitor)



cVu-V VxLAN ports



current

cVu-V: 10.0.1.129 Port: cvuv_net_dev_vxlan0	24.2 Mbps
cVu-V: 10.0.1.130 Port: cvuv_net_dev_vxlan0	8.3 Mbps
cVu-V: 10.0.1.131 Port: cvuv_net_dev_vxlan0	15.0 Mbps
cVu-V: 10.0.1.129 Port: cvuv_net_dev_vxlan1	24.2 Mbps
cVu-V: 10.0.1.130 Port: cvuv_net_dev_vxlan1	8.3 Mbps
cVu-V: 10.0.1.131 Port: cvuv_net_dev_vxlan1	15.0 Mbps

# Thank You

LOREM  
+0.7844

IPSUM  
-4.5489

DOLOR  
+6.2035

SIT  
-0.8965

AMET  
+3.0293

CONSECT  
-9.2904

ADIPISCING  
-8.3748

+Add



25.820

18.775

+4.006

+5.434

+2.903

-0.438

+3.110

-8.325